



Incredible 1 million candle power in a small housing

- Ceramic base and chip technology
- Will help save costs and increase efficiency
- Vibration resistant housings

RC= Remote Controlled

(Hard Wired)

- Manufactured for use in harsh environments
- Operates at a fraction of the temperature of conventional spotlights



SL-65W - {RC RRC

RRC(Radio Remote Controlled)

SPECIFICATIONS:

Light Source:	65 Watt Ceramic LED	Color Rendering Index:	>85 CRI
Power Consumption:	65 Watt	Operating Voltage:	AC 100-305V 50-60HZ
Intensity:	1,000,000 cp	Material Fixture:	Aluminum
Effciency:	91% typ	Mounting Bracket:	A4 316 Stainless Steel 4MM
Lumens Per Watt:	150 Lms./Watt	IP Rating:	IP68
Beam Angle:	9° at 10% intensity	Finish:	Seawater resistant powder coating
LED Color:	3900K Natural White	Dimensions:	11-1/2" W x 9-1/2"H x 7-1/4" (Bracket) to 6-1/2"D (w/o) Bracket)
Models - SL-65W $\left\{ \begin{array}{c} RC \\ RRC \end{array} \right\} - \left\{ \begin{array}{c} 12VDC \\ 24VDC \\ 120VAC \end{array} \right\}$			
* DC- Domote Controlled (Llord Wired) DDC-Dedie Domote Controlled			

* RC= Remote Controlled (Hard Wired)

RRC=Radio Remote Controlled



1639 Stephen Street, Ridgewood, NY 11385 Tel. (718) 456-3606 Fax (718) 381-0229 www.mcdermottlight.com

