



## PLAT-SOLAR

High Intensity Solar Light for  
Bridges, Channel Markers, Buoys, etc.



**PLAT-SOLAR**  
**Platform Mount**

### SPECIFICATIONS:

**Range:** 2 - 6 miles available (See Chart Below)

**Light Source:** High-power LED available in white, red, green, and amber with a rated life of 50,000 hours

**Material:** High-impact UV stabilized polycarbonate

**Battery:** Rechargeable battery pack with average life of 4-5 years

**Mount:** Raised platform mount

**Flash Rates:** 10, 15, 24, 30, 60 FPM or steady and any IALA flash pattern

**\*Warranty:** One year parts and labor at no charge, except for physical damage or abuse

ENCLOSURE	CONFIG	DRAIN	MODE	RANGE	CANDELA POWER	COLOR	FLASH RATES
PLAT-SOL	18L11V	0.03	STEADY	3	31.20	WHITE	10, 15, 24, 30, & 60 FPM
		0.08	FLASHING	4	72.50		
		0.15	FLASHING	5	103.60		
PLAT-SOL	18L11V	0.03	STEADY	3	28.00	GREEN	10, 15, 24, 30, & 60 FPM
		0.08	FLASHING	4	60.10		
		0.15	FLASHING	5	98.70		
PLAT-SOL	18L11V	0.03	STEADY	3	35.50	RED	10, 15, 24, 30, & 60 FPM
		0.08	FLASHING	4	71.90		
		0.15	FLASHING	5	117.70		
PLAT-SOL	18L11V	0.03	STEADY	3	29.90	AMBER	10, 15, 24, 30, & 60 FPM
		0.08	FLASHING	4	53.30		
		0.15	FLASHING	5	83.60		

\*PLAT = PLATFORM MOUNT

\*NM = NAUTICAL MILES

\*SPK = 3 BIRD SPIKES

